



## **MOTOR GOLD Super Tractor Universalöl STOU SAE 10W-30**

**MOTOR GOLD Super Tractor Universalöl STOU SAE 10W-30** is a special type of oil, which complies with the recommendations of well-known general purpose tractor manufacturers. It can be used equally well in engines, gear and hydraulic systems of modern tractors. High quality base oils and selected additives ensure trouble-free operation of all systems throughout the year. It is likewise suitable for wet brakes and clutches (PTO - power shaft clutches).

### **ACEA-/API-specifications:**

API CG-4 (obsolete)  
API CF-4 (obsolete)  
API CF (obsolete)  
API CE (obsolete)  
API CD (obsolete)  
API SF (obsolete)  
API GL 4

### **Meets/suitable for use:**

(Meets the requirements of the OEM-Approval. An approval by name from the manufacturer is not present.)

#### STOU:

ZF TE-ML 03A, 05K, 06B, 06C, 07B, 07D  
Massey Ferguson M1145, M1144, M1139  
Ford M2C159 B/C  
New Holland NH030C, 82009201  
John Deere J27

#### UTTO:

Massey Ferguson M1135  
John Deere J27C  
Ford M2C86B, M2C134D  
New Holland NH410B  
Allison C4 (level)  
Caterpillar TO-2 (level)

#### Hydraulik:

Sperry Vickers/Eaton M29505, I-280-S  
Sauer Sunstrand/Danfoss Hydrostatic Trans Fluid



### Typical characteristics *MOTOR GOLD Super Tractor Universaloeel STOU SAE 10W-30:*

(The given data are typical data. Please observe operating prescriptions.)

Parameter	Method	Unit	
SAE class	SAE J 300		10W-30
Density 15 °C	DIN EN ISO 12185	g/cm <sup>3</sup>	0.863 – 0.873
Kin. viscosity @ 40 °C	DIN 51562 -1	mm <sup>2</sup> /s	68.7
Kin. viscosity @ 100 °C	DIN 51562-1	mm <sup>2</sup> /s	10.5
Viscosity index	DIN ISO 2909		139
Total Base Number	DIN ISO 3771	mg KOH/g	11.0
Dyn. viscosity @ -25°C	DIN 51377	mPa*s	6,300
Flash point COC	DIN ISO 2592	°C	min. 220
Pour Point	DIN ISO 3016	°C	-48

### Available Packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4*5 Liter	4*4 Liter	12*1 Liter
<i>MOTOR GOLD Super Tractor Universaloeel STOU SAE 10W-30</i>			•		•			

<sup>1</sup>Version 6 – 10/2017

<sup>1</sup> This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.