



MOTOR GOLD Lightrun 2000

MOTOR GOLD Lightrun 2000 is a fuel economy motor oil which can be used all year round in many types of passenger car gasoline or diesel engines or heavy duty commercial vehicles with normally aspirated or turbocharged diesel engines.

MOTOR GOLD Lightrun 2000 contains synthetic base oils and modern additives. It guarantees very long drain intervals and high wear protection with low oil and fuel consumption.

ACEA/API-specifications:

ACEA E7

ACEA A3/B3

ACEA A3/B4

API CI-4

API SL

OEM-Approvals:

MB-Freigabe 228.3

MB-Freigabe 229.1

MAN M 3275-1

Meets/suitable for use:

(Meets the requirements of the OEM-Approval. An approval by name from the manufacturer is not present.)

Cummins CES 20077/78

Detroit Diesel DDC 93K215

Deutz DQC III-10

Mack-EO-N, Mack-EO-M Plus

MTU Type 2

Renault RLD-2

Voith A

Volvo VDS-3

Allison C4

Global DHD-1

JASO DH-1





Typical characteristics MOTOR GOLD Lightrun 2000:

(The given data are typical data. Please observe operating prescriptions.)

Parameter	Method	Unit	
SAE class	SAE J 300		SAE 10W-40
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.868
Kin. viscosity @ 40 °C	DIN 51562 -1	mm ² /s	94.2
Kin. viscosity @ 100 °C	DIN 51562-1	mm ² /s	14.7
Viscosity index	DIN ISO 2909		163
Total Base Number	DIN ISO 3771	mg KOH/g	10.0 – 12.0
Dyn. viscosity @ -25°C	DIN 51377	mPa*s	max. 7,000
Flash point COC	DIN ISO 2592	°C	min. 210
Pour Point	DIN ISO 3016	°C	-36

Available Packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4*5 Liter	4*4 Liter	12*1 Liter
MOTOR GOLD Lightrun 2000		•	•		•			

¹Version 8 – 01/2018

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.

AVISTA OIL Deutschland GmbH

Bahnhofstrasse 82 · D-31311 Uetze, Germany

Tel. +49 5177 85-0 · Fax +49 5177 85-230 · Internet: www.motorgold.de