



MOTOR GOLD Supertec SAE 5W-40

MOTOR GOLD Supertec SAE 5W-40 is a motor oil aimed for the fuel efficient/economy operation of engines. To guarantee the performance of the SAE 5W-class together with low volatility it consists entirely of HC-synthesis-technology base oils which meet the high technological demands of the latest engine generation.

MOTOR GOLD Supertec SAE 5W-40 is for the fuel-efficient, all-year use in modern passenger car gasoline and diesel engines. It is developed for turbocharged engines as well as for cars with a catalyst.

ACEA-/API-specifications:

ACEA A3/B4

API SN

API CF (obsolete)

OEM-Approvals:

MB-Freigabe 229.3

VW 502 00, 505 00

Porsche A40

Meets/suitable for use:

Renault RN 0700 / RN 0710

BMW Longlife-01 (level)

GM-LL-A/B-025 (level)

JASO MA2 (level)



			MOTOR GOLD Supertec SAE 5W-40
Parameter	Unit	Testing method	SAE 5W-40
Density 15°C	kg/m ³	DIN EN ISO 12185	857
Flash point COC	°C	DIN ISO 2592	min. 200
Pour point	°C	DIN ISO 3016	-39
Viscosity 40°C	mm ² /s	DIN 51562-1	85.2
Viscosity 100°C	mm ² /s	DIN 51562-1	14.3
VI		DIN ISO 2909	175

12/2017

Version 5

The given data are typical data. Please observe operating prescriptions.

Available packaging:

	997 Liter	208 Liter	60 Liter	20 Liter	4 * 5 Liter	4 * 4 Liter	12 * 1 Liter	Notes:
MOTOR GOLD Supertec SAE 5W-40	•	•	•	•	•	•	•	

1

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL Group or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.

2