



MOTOR GOLD Supertec Sport SAE 5W-50

MOTOR GOLD Supertec Sport SAE 5W-50 is a motor oil aimed for the fuel efficient/economy operation of engines. To guarantee the performance of the SAE 5W-class together with low volatility **MOTOR GOLD Supertec Sport SAE 5W-50** consists entirely of HC-synthesis-technology and PAO base oils which meet the high technological demands of the latest engine generation.

MOTOR GOLD Supertec Sport SAE 5W-50 is for the fuel efficient, all-year use in modern passenger car gasoline and diesel engines and was developed for turbocharged engines as well as for cars with a catalyst.

Meets/suitable for use:

ACEA A3/B4

API SN

API CF (obsolete)

Typical characteristics MOTOR GOLD Supertec Sport SAE 5W-50:

(The given data are typical data. Please observe operating prescriptions.)

Parameter	Method	Unit	
SAE class	SAE J 300		SAE 5W-50
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.855 – 0.865
Kin. viscosity @ 40 °C	DIN 51562 -1	mm ² /s	106
Kin. viscosity @ 100 °C	DIN 51562-1	mm ² /s	17.1
Viscosity index	DIN ISO 2909		176
Total Base Number	DIN ISO 3771	mg KOH/g	10.0 – 12.0
Dyn. viscosity @ -30°C	DIN 51377	mPa*s	max. 6,600
Flash point COC	DIN ISO 2592	°C	min. 200
Pour Point	DIN ISO 3016	°C	max. -36



Available Packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4*5 Liter	4*4 Liter	12*1 Liter
<i>MOTOR GOLD Supertec Sport SAE 5W-50</i>								•

Special viscosity grade: min. 2,000 L

¹Version 2 – 01/2019

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.