



MOTOR GOLD Fluitec TYP P/CN

MOTOR GOLD Fluitec Typ P/CN is an automotive transmission fluid for use in automatic transmissions as well as power steering and leveling systems in passenger cars, busses, trucks and construction site equipment.

- suitable for steering booster and hydraulics

OEM-Approvals:

MB-Freigabe 236.1 (beantragt)
MAN 339 Type L-1
MAN 339 Type V-1
MAN 339 Type Z-1
ZF TE-ML 03D, 04D, 14A & 17C (ZF002311)

Meets/suitable for use:

(Meets the requirements of the OEM-Approval. An approval by name from the manufacturer is not present.)

DEXRON® II-D
GM Motors Type A Suffix A (TASA)
MERCON®
Voith 55.6335.xx
ZF TE-ML 11B
Allison C-4 (level)
Caterpillar TO-2 (level)
Renk Domorat (level)



Typical characteristics MOTOR GOLD Fluitec TYP P/CN:

(The given data are typical data. Please observe operating prescriptions.)

Parameter	Method	Unit	
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.852 – 0.862
Kin. viscosity @ 40 °C	DIN 51562 -1	mm ² /s	41.3
Kin. viscosity @ 100 °C	DIN 51562-1	mm ² /s	8.2
Viscosity index	DIN ISO 2909		178
Total Base Number	DIN ISO 3771	mg KOH/g	2.6
Brookfield @ -40 °C	DIN 53598	mPa*s	21,700
Flash point COC	DIN ISO 2592	°C	≥ 220
Pour Point	DIN ISO 3016	°C	≤ -48

Available Packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4*5 Liter	4*4 Liter	12*1 Liter
MOTOR GOLD Fluitec TYP P/CN			•		•			•

¹Version 6 – 01/2018

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.