



MOTOR GOLD HYDRAULIC OIL HLP-D

MOTOR GOLD HYDRAULIC OIL HLP-D is based on paraffinic base oil and modern additive technology. Effective zinc containing components guarantee optimal lubrication and long term protection against oxidation. During the process fine filtration is possible without the risk of losing valuable ingredients. Because of the high viscosity index the lubricating effect of the oil remains unaffected even at very high temperatures.

Dispersant and detergent additives provide optimal dirt-removing properties and the product is especially suitable for centrally supplied machines.

Specifications:

DIN 51524-2 (except demulsification)
FZG-Test A 8,3/90 load stage: >12

Typical characteristics HYDRAULIC OIL HLP-D

(The given data are typical data.)

Parameter	Method	Unit	ISO VG 32	ISO VG 46	ISO VG 68
Density 15 °C	DIN EN ISO 12185	g/cm ³	859	866	873
Flash point COC	DIN EN ISO 12185	g/cm ³	220	230	240
Pour Point	DIN 51562 -1	mm ² /s	-27	-27	-24
Viscosity @ 40 °C	DIN 51562-1	mm ² /s	31,5	44,8	67,2
Viscosity @ 100 °C	DIN 51562-1	mm ² /s	5,6	6,8	9,0
Viscosity index	DIN ISO 2909		114	113	109

Available Packaging:

	Bulk	965 Liter	208 Liter	60 Liter	20 Liter	4*5 Liter	4*4 Liter	12*1 Liter
HYDRAULIC OIL HLP-D	•	•	•		•			

1

Version 3 – 02/2018

¹ This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.