



## **MOTOR GOLD Fluitec ATF 6000**

**MOTOR GOLD Fluitec ATF 6000** offers premium quality in the sector of automatic transmission oils. This ATF oil meets or exceeds the requirements in car applications with torque converters or wet clutches as well as power steering systems.

**MOTOR GOLD Fluitec ATF 6000** fulfills the latest GM specification DEXRON® VI and is backwards compatible with older DEXRON® specifications (e.g. DEXRON®-III H, III, II).

**MOTOR GOLD Fluitec ATF 6000** provides excellent low temperature performance, improved thermal and oxidative stability as well as extended fluid and clutch life.

### **Meets/suitable for use:**

(Meets the requirements of the OEM-Approval. An approval by name from the manufacturer is not present.)

DEXRON® VI

MERCON® LV

Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)

Audi/VW G 052 162-A1/A2, G 053 025-A2, G 052 025-A2, G 055 025 A2 (JWS 3309)

Audi/VW G 052 162 (ZF Lifeguardfluid 5) (ZF No. S671 090 170)

Audi/VW G 060 162 (ZF Lifeguardfluid 8) (ZF No. S671 090 312)

Audi/VW 052 055, G 055 540 (A2), G 052 990

BMW ZF 5HP18FL, 5HP24, 5HP30

BMW 7045E, ETL 8072B

BMW MINI

Bosch TE-ML 09

Chrysler/Dodge/Jeep 05127382AA, 68043742AA, 68171866AA

FIAT T-IV type, JWS 3309

GM9986195 (Aisin AW, JWS 3309)

Jaguar ATF 3403, JLM20238, K17, JLM 20292, Fluid 8432

Land Rover LR023288

MAN 339A

Porsche 999 917 547 00 (A2), Z 000169756

Porsche 000 043 205 28, 000 043 205 09

Renault Samsung SATF-D, Matic D2, DPO/AL4

Volvo PN 1161521, PN 1161521, PN 1161540/1161640

Volvo 97335, 97325, CE 97340

VW 5HP (19FL, 24A), (18FL, 30), (ZF 5 HP 30)

ZF 9 speed transmissions, 8 speed transmissions, all 3 & 4 speed transmission

ZF TE-ML 05L, 09, 11A, 11B, 21L



## Typical characteristics MOTOR GOLD Fluitec ATF 6000:

(The given data are typical data. Please observe operating prescriptions.)

| Parameter               | Method           | Unit               |               |
|-------------------------|------------------|--------------------|---------------|
| Density 15 °C           | DIN EN ISO 12185 | g/cm <sup>3</sup>  | 0.839 – 0.849 |
| Kin. viscosity @ 40 °C  | DIN 51562 -1     | mm <sup>2</sup> /s | 28.2          |
| Kin. viscosity @ 100 °C | DIN 51562-1      | mm <sup>2</sup> /s | 5.8           |
| Viscosity index         | DIN ISO 2909     |                    | 153           |
| Total Base Number       | DIN ISO 3771     | mg KOH/g           | 2.4 – 3.0     |
| Brookfield @ -40 °C     | ASTM D 2983      | mPa*s              |               |
| Flash point COC         | DIN ISO 2592     | °C                 | min. 220      |
| Pour Point              | DIN ISO 3016     | °C                 | max. -48      |

## Available Packaging:

|                                | Bulk | 965<br>Liter | 208<br>Liter | 60<br>Liter | 20<br>Liter | 4*5<br>Liter | 4*4<br>Liter | 12*1<br>Liter |
|--------------------------------|------|--------------|--------------|-------------|-------------|--------------|--------------|---------------|
| MOTOR GOLD<br>Fluitec ATF 6000 | •    | •            | •            | •           | •           |              |              | •             |

<sup>1</sup>Version 4 – 07/2018

<sup>1</sup> This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AVISTA OIL or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale.

**AVISTA OIL Deutschland GmbH**

Bahnhofstrasse 82 · D-31311 Uetze, Germany

Tel. +49 5177 85-0 · Fax +49 5177 85-230 · Internet: [www.motorgold.de](http://www.motorgold.de)